

Package: viafr (via r-universe)

August 28, 2024

Title Interface to the 'VIAF' ('Virtual International Authority File') API

Version 0.3.1

Maintainer Stefanie Schneider <stefanie.schneider@itg.uni-muenchen.de>

Description Provides direct access to linked names for the same entity across the world's major name authority files, including national and regional variations in language, character set, and spelling. For more information go to <<https://viaf.org/>>.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

URL <https://github.com/stefanieschneider/viafr>

BugReports <https://github.com/stefanieschneider/viafr/issues>

Suggests testthat (>= 2.1.0), roxygen2

Imports utf8, crul, jsonlite, assertthat, magrittr, stringr, tibble, tidyverse, purrr, dplyr, rlang

Depends R (>= 2.10)

Repository <https://stefanieschneider.r-universe.dev>

RemoteUrl <https://github.com/stefanieschneider/viafr>

RemoteRef HEAD

RemoteSha c9b15beb65a6c114cd6a8a1ee05e7ea77076d70e

Contents

authorities	2
name_types	2
viaf_get	2
viaf_search	3
viaf_suggest	4

Index

5

authorities	<i>VIAF Authorities</i>
-------------	-------------------------

Description

A dataset containing the names and schemes of 55 organizations and libraries that participate in the VIAF.

Usage

```
data(authorities)
```

Format

A tibble with 55 rows and 2 variables.

name_types	<i>VIAF Name Types</i>
------------	------------------------

Description

A dataset containing the 5 possible name types in the VIAF.

Usage

```
data(name_types)
```

Format

A tibble with 5 rows and 2 variables.

viaf_get	<i>Get Data for VIAF Identifier(s)</i>
----------	--

Description

Get authority cluster data based on supplied VIAF identifier(s).

Usage

```
viaf_get(query = NULL, ...)
```

Arguments

- | | |
|-------|---|
| query | The VIAF identifier(s) to get data for. |
| ... | Optional VIAF API query parameters. |

Value

A tibble with data items.

Note

An internet connection is required. The MARC 21 field definitions are used. This function does not currently work due to changes to the VIAF.

Examples

```
## Not run: viaf_get(c("64013650", "102333412"))
```

viaf_search

Search VIAF records

Description

Search VIAF records where the authority includes the given terms.

Usage

```
viaf_search(query = NULL, ...)
```

Arguments

- | | |
|-------|--|
| query | The search query (or queries) to get data for. |
| ... | Optional VIAF API query parameters. |

Value

A named list of tibbles with data items.

Note

An internet connection is required. The MARC 21 field definitions are used.

Examples

```
viaf_search(c("Rembrandt", "Jane Austen"))
```

viaf_suggest	<i>Suggest VIAF records</i>
--------------	-----------------------------

Description

Suggest VIAF records based on given terms passed in a query.

Usage

```
viaf_suggest(query = NULL, ...)
```

Arguments

query	The search query (or queries) to get data for.
...	Optional VIAF API query parameters.

Value

A named list of tibbles with data items.

Note

An internet connection is required.

Examples

```
viaf_suggest(c("rembrandt", "austen"))
```

Index

* datasets

authorities, [2](#)

name_types, [2](#)

authorities, [2](#)

name_types, [2](#)

viaf_get, [2](#)

viaf_search, [3](#)

viaf_suggest, [4](#)